



S-OIL dragon CD/SF 20W-50

MULTI GRADE OIL FOR DIESEL ENGINE OIL

Product Description

DRAGON CD/SF is suitable to all turbocharged or normally aspirated Diesel engines of civil works machines, trucks, fishing boats, locomotives, Diesel stationary engines (energy production). It is also suitable for gear boxes, torque converters, hydraulic systems when manufacturer requires engine oil with an appropriate grade for these applications.

Applications

- All turbocharged or normally aspirated diesel engines for all services when the manufacturer has no special requirement.

Features and potential benefits

- Multi-grade oil
- High viscosity index
- Good level of detergency
- Exceptional detergency level
- High stability in operation
- Excellent antiwear and anticorrosion properties
- Excellent antioxidant, antirust and antifoaming properties.

Performance level

- API CD/SF

Typical Properties

Test Items	Method	Unit	20W-50
Specific gravity	ASTM D1298	-	0.8820
Viscosity	40°C ASTM D445	cSt	165.7
	100°C ASTM D445	cSt	18.5
Viscosity index	ASTM D2270	-	125
Flash point	ASTM D92	°C	250
H.T.H.S viscosity	ATSM D4683		4.8
Pour point	ASTM D97	°C	-25

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

DRAGON CD/SF 20W-50
2016.12.13.



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.